

## PART 1: GENERAL

### 1.1 Summary

This section includes written specifications for the MBV-1, MBV-1-OPEN, MBV-1-VISI, MBV-2, MBV-2- OPEN, MBV-2-VISI and MBV-XL expanded metal bicycle cage lockers.

### 1.2 Quality Assurance

#### A. Manufacturer Qualifications:

1. A manufacturer experienced in manufacturing and producing commercial bicycle parking racks similar to the desired specification described for this project and with a record or successful in-service performance.
2. Product Options: The manufacturer will be able to produce several finish and color options, and types of the bicycle racks from a single source or from resources able to provide product options of like quality in both form and function.
3. Manufacturer Service Options: The manufacturer will be able to present product specific drawings of the bicycle racks size, shape, dimensional requirements, and weight.

#### B. Installer Qualifications: Experienced installer has completed installation of bicycle racks similar in specifications and to the extent indicated for this project.

### 1.3 Submittals

- A. Product Information: Must contain physical descriptions such as bicycle parking capacity, dimensions, shape, installation hardware requirements, and finish options for each bike rack.
- B. Installation Drawings and/or Installation Video: Details installation instruction for the designated bicycle rack. Drawing packages and submittals can be supplied by Ground Control Systems.
- C. Assembly Instructions: For the MBV-1, MBV-1-OPEN, MBV-1-VISI, MBV-2, MBV-2- OPEN, MBV-2-VISI and MBV-XL expanded metal bicycle cage lockers.
- D. Product Verification: Able to submit finish samples for review and verification upon request.
- E. Manufacturer's Project References: Able to provide a minimum of three references for whom the firm provided similar or comparable services during the last 5 years and a description of the services provided.
- F. Warranty: Submit manufacturer's standard warranty.

### 1.4 Delivery, Storage, and Handling

- A. Delivery: In order to ensure shipments are received undamaged, a thorough inspection must be performed and noted on the B.O.L. upon receipt of shipment.
- B. Storage: Bicycle racks and components should be stored in their original packages or containers until they are ready for installation.
- C. Handling: Before and up to installation, bicycle racks should be handled with sufficient care in order to prevent any finish damage.

### 1.5 Warranty

Manufacturer's Warranty: Bicycle racks carry a one year limited warranty against defects in materials and workmanship beginning on the date they receive

## PART 2: PRODUCTS

### 2.1 Manufacturer

Provided bicycle racks designed by Ground Control Systems®, 708 Alhambra Blvd, Suite 200, Sacramento, CA, 95816, 1-800-630-7225, Fax: 1-866-532-9049, Website: [www.groundcontrolsystems.com](http://www.groundcontrolsystems.com).

### 2.2 Materials

- A. MBV-1, MBV-1-OPEN, MBV-1-VISI, MBV-2, MBV-2- OPEN, MBV-2-VISI and MBV-XL expanded metal bicycle cage lockers:
1. All material is ASTM A36, A53 and/or A500.
  2. Aluminum, zinc and stainless steel hardware.

### 2.3 Finishes

- A. DV215 Varsity® Head:
1. DuraPlas ®finish – Standard Black Thermoplastic.
  2. Hot Dipped Galvanized finish (marine environment).
- B. MBA Base:
- UV resistant Metallic Grey powder coating (Standard, Marine Environment rated)

### 2.4 Space Use

- A. MBV Setbacks:
1. Wall setback: For lockers set parallel or perpendicular to a side wall: less than 3" or greater than 9" \*
  2. Distance between lockers: less than 3" or greater than 9" \*
  3. Front of locker to wall: minimum 48", recommended 60"
- \* Child safety requirements

### 2.5 Product Details

- A. MBV-1 (Solid Door & Walls - 1 Bike)
- B. MBV-1-OPEN (Standard, Perforated Door & Solid Walls - 1 Bike)
- C. MBV-1-VISI (Perforated Door & Walls - 1 Bike)
- D. MBV-2 (Solid Door & Walls - 2 Bikes)
- E. MBV-2-OPEN (Standard, Perforated Door & Solid Walls - 2 Bikes)
- F. MBV-2-VISI (Perforated Walls & Door - 2 Bikes)
- G. MBV-XL (Standard, Perforated Door & Solid Walls - 1 Bike (Tandem, Wide Cargo Bike, Bikes w/ Trailers))

## PART 3: EXECUTION

### 3.1 Examination

Examine footprint to ensure conditions are adequate for installation. Do not proceed with installation if conditions are not adequate for installation. Notify the project manager if conditions are unsatisfactory.

### 3.2 Preparation

Make sure the location of the bike racks is flat, level, square, accurate for alignment, and correctly located for the installation of the bike racks. Shimming may be necessary for tapered and uneven grades.

### 3.3 Installation

Surface or Flange Mount: An above ground mount anchored into concrete or asphalt using anchors specific to the surface. Requires four 3" x 3/8" Wedge Anchor kits. Contact Ground Control for additional mounting options.

### 3.4 Quoting

- A. Product Specification: Make sure the product item, finish options, installation hardware, fasteners, and expected lead time have been included in the estimate.
- B. Product Pricing: Quotes are in US Dollars and valid for 90 days.
- C. Product Pricing: Quotes for Special Orders are valid for 30 days. (Special orders are purchases containing non-stocking products, custom colors, or quantities higher than what is typically on hand.
- D. Shipping Pricing: Shipping Quotes are estimates and only good for 30 days - cost may fluctuate up to 25%.

### 3.5 Freight

- A. MBV-1, MBV-1-OPEN, MBV-1-VISI, MBV-2, MBV-2- OPEN, MBV-2-VISI and MBV-XL expanded metal bicycle cage lockers ship freight LTL. Call Ground Control Systems at 1-800-630-7225 for a formal quote.
- B. Shipment Pricing: Estimates are good for 30 days; contact a Ground Control Systems representative for a current price list.

### 3.6 Purchasing

- A. Product specification: Make sure the product item, finish options, fasteners, and expected lead time have been included in the estimate.
- B. Pricing: Estimates are good for 90 days (30 days for special orders); contact a Ground Control Systems representative for a current price list if the estimate has expired.
- C. Shipping Pricing: Shipping Quotes are estimates and only good for 30 days - cost may fluctuate 25%.
- D. Placing an order: You can order via phone 1-800-630-7225; Fax 1-866-532-9049; Email - [info@groundcontrolsystems.com](mailto:info@groundcontrolsystems.com). Or, if submitting purchase orders, mail to: 708 Alhambra Blvd, Suite 200, Sacramento, CA, 95816.